

Product: SONAX Profiline Paint Prepare

Article Code: 237 300 Formula Code: 6531 2000

Product description: Solvent based cleaner for the fast and effective removal of grease, oil

and silicone dirt from paintwork surfaces. It prepares the paintwork for long lasting sealing with SONAX Nano Paint Protect (Art. No. 236 000). It is also ideal for checking the results obtained from hologram-free polishing, for de-waxing paintwork surfaces and as final cleaning

prior to painting.

Areas of Application: As preparation for SONAX Nano Paint Protect (Art No. 236 000): Use

after hologram-free polishing. It cleans the paintwork surface and removes all polish residues, which may impair the effects of the long

lasting paintwork sealant SONAX Nano Paint Protect.

As control spray during the polishing process: Use after the final polishing stage. With the appropriate lighting, it reveals even the tiniest

polishing flaws and holograms.

For de-waxing paintwork surfaces: It removes all remaining polish, as

well as wax, oil and silicone residues.

Directions for Use: -Shake can before use.

-Thinly spray SONAX Profiline Paint Prepare onto the dry paintwork surface, wipe off immediately afterwards with SONAX Microfibre Cloth.

PLEASE NOTE:

Only apply onto painted surfaces. Do not use on hot paintwork surfaces. Observe caution when re-spraying, first test paint for

fastness.

Chemical Characterisation: blend of solvents

Specific data: Appearance: colorless liquid

Density: 0.75 - 0.77 g/ml

Viscosity: 10 - 12 s (Ford cup 4mm)

pH: ---

Packaging: Aerosol can 400ml

Safety data: See safety data sheet

Source: 1techdat\datenblaetter\ Date: 11.12.2017 Printed: 4/29/2021 File: 237300e.doc Made by: EF/ M. Pitsch Revision: 0