

**Product:** **SONAX ProfiLine UltimateCut**

**Article Code:** **239 300/500**

**Formula Code:** 2390 0147

**Product Description:** Highly effective abrasive paste for polishing heavily weathered or partially sanded paintwork layers. Smoothens out scratches and abrasions and removes paint overspray. Removes sanding marks from P1000 grain size abrasive paper, but is very low in dust. Low Dust Technology.  
Enables longer processing times and subsequent attainment of an even higher gloss level.  
Abrasive performance: 6  
Gloss level: 3

**Directions for Use:**

- Wash vehicle thoroughly and wipe dry.
- A polishing machine with variable rotational speed and with red Polishing sponge 160 (hard) is recommended or, alternatively, the Lambskin pad 130.
- Guide the polishing machine initially at low rotational speed (800 rpm), exerting somewhat higher pressure, then reduce pressure and for polishing out, press the machine lightly in the process increasing to a medium rotational speed (1500 rpm max.). This will attain an even higher gloss level.
- Remove polish residues completely with a microfibre cloth.
- To improve the gloss level on the treated area, polish it once again with **SONAX Perfect finish** or **SONAX EX 04-06** in case of use of a DA-polisher.

**Please Note:**

- Do not apply in direct sunlight or onto warm surfaces.
- Protect against extreme cold.
- Do not polish a smaller area for too long, as there is a danger of producing a polishing spot or even polishing through the lacquer.

**Chemical Classification:** Emulsion containing abrasives, silicone free, wax free.

**Specific Data:**

Appearance:	White, viscous fluid
Density:	1.05 – 1.15 g/ml
Viscosity:	10 – 15 Pas (Brookfield Sp. 6/20 rpm)

**Packaging:**

1 L PE Bottle	<b>(239 300)</b>
5 L PE canister	<b>(239 500)</b>

**Safety Data:** See safety data sheet